

## **GENERAL INFORMATION:**

The **SHO-ME**<sup>®</sup> LED Stretch Bar is equipped with a Solid State Flasher. The flasher has 7 flash patterns including random. To change flash patterns momentarily apply +12v to the white, mode wire. Each time +12v is applied, the flash pattern will change.

## **FLASH PATTERNS**

AltQuad Single 120 Single 240 Dual Rotate Single Rotate Fast Sequence All & Steady Single scan 2 25 ms on, 25 ms off Beacon Fade 90 FPM Alt Double On Quad On SuperMega then steady Random All Non Sequential patterns Random All Patterns

## **INSTALLATION INSTRUCTIONS:**

Determine location to mount your LED Stretch Bar. Attach bolts to bottom of your **SHO-ME**<sup>®</sup> LED Stretch Bar. Keep in mind airbag deployment area and any other obstacles. Run wire inside of vehicle and connect to switch. A momentary switch is required to change flash patterns.

If mounting this product requires drilling holes, the installer MUST be sure that no vehicle components or other vital parts could be damaged by the drilling process. Check both sides of the mounting surface before drilling begins. Also de-burr any holes and remove any metal shards or remnants. Install grommets into all wire passage holes.

Use only soap and water to clean the outer lens. Use of other chemicals could result in premature lens cracking and discoloration. Lenses in this condition have significantly reduced effectiveness. Inspect and operate this product regularly to confirm its proper operation and mounting condition. **Do not use a pressure washer to clean this product**.



PRODUCTS COMPANY • 804 East Hwy. 248 • Casavilla, NO 85825 U.S. and Canada Toll Free Numbers • Phone: 800-641-4096 FAX: 800-526-1240 E-mail: sales@able2products.com WEB: www.able2products.com

20				
		19 18		
8		13		14
	J, j	17	1	
	· · ·		ť	15
				5
				م ۲۱ م
				9
21-22				· / <sup>4</sup>
	10			
				ו•
6-7				
,23 5			⊲ ∖∙	
		16		
	- · Dart	s List for 11.1237		
LED Stretch Bar				
		rmanent Mount		
ITEM	MODEL NO.	DESCRIPTION	QTY	
1	90.4986.000	31" Long Extrusion	1	
2	90.6137.C00	Clear Lexan End Cover	2	
3 4	90.6125.000	Black Plastic Endcaps Long Black Plastic LED mount	2 4	
5	90.6938.000 90.6931.000	Short Black Plastic LED mount	4 2	
6	95.3750.(R/A)00	Red/Amber LED Board	2	
7	95.3751.BOO	Blue/White LED Board	2	
8	90.4002.000	#01-0143 #8 x 1/ 2 812 Screw	18	
9	90.4072.000	1/ 4" #6-32 Phillips	20	
10	90.4772.000	8-32x3/ 8 Unslot HexHD SS	18	
11 12	90.4021.SS	Endcap Self Tapping Screws	4 4	
12	90.4530.000 90.6039.000	#8 External Tooth Lock washer 1/ 8" X 3/ 4" Blk Foam Adhesive		
13	11.1010.SF	LED Flasher 4-output	1	
15	61.0651.000	7" Cable Ties	12	
16	95.2120.000	Rubber Shim	4	
17	90.6938.000	2-3/ 4" Cut Plastic	4	
18	90.6138.000	Jointer Piece	3	
19	90.6747.000	Rubber Gasket 1' ea	6	
20	90.6136.000	Clear Lexan 10" Middle Lens	2	
21 22	95.3750-1.(R/A)00 95.3751-1.BOO	Red/Amber LED Board Blue/White LED Board	4	
22	44.0183.000	Power Cable 4 Wire 15 ft	4	11-07
				11-07