LIGHT STORM®

LED Signal Stick MODEL NO. 12.6204KIT-2

GENERAL INFORMATION

The LED Signal Stick points traffic in the direction they need to follow. The Signal Stick comes complete with controller (Model No. 11.1000-2). The controller has an ON/OFF Switch, Rotary Switch and Speed Control Dial. **NOTE:** Shielded wire must be grounded at the Controller. The LED Signal Stick has twelve flash patterns from which to choose:

- 1. Double Alt
- 2. Double Alt*
- 3. Quad Alt
- Quad Alt*

- 5. Single Alt*
- 6. Single Alt
- 7. Random
- 8. Left

- 9 Left*
- 10. Right
- 11 Right*
- 12. Center Out

INSTALLATION INSTRUCTIONS

Use the L - brackets (included) to mount the lights. Slide the hex bolts provided into the t-slot as shown in the Figure A below. The light can be mounted using the bottom or rear t-slots. Always mount with the bottom t-slot down, this is to allow any moisture that enters the light housing to drain properly.

WIRING INSTRUCTIONS

Black wire to Ground, Red wire to Positive +12V. Yellow wire activates the signal sticks in a Random Flash Pattern when +12v is applied. When operating signal sticks with controller, All Signal Stick functions will override the Random Flash.

